

## OAK NOUVEAU INK

The rich brown tones in this single-strip oak floor from the Classic Nouveau Collection allow the warmer hues to come through resulting in an elegant and refined expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided micro-bevelling at the edges ensures a classic full plank look and feel. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES			
Article Number	151N9AEK19KW200	Wood Species	Oak	Moisture	EN13183	7%±2%	
Surface treatment	Matt lacquer	Board	1-strip	content			
Design features	Brushed, Microbevelled 4- sided	Grading	Lively (Country)	Minimun Mean Density kg/m <sup>3</sup>			>500 kg/m³
		Range	Kährs Original	Reaction To	EN13501-1	Dfl-s1	
Dimensions	2000 x 187 x 15 mm	Collection	Classic Nouveau	Fire Formaldehyde Emission Content PCP Breaking	EN717-1	E1 ≤ 5 x 10-6n	
Weight per Package	18 kg		Collection				
Area per Package	2.24 m <sup>2</sup>	Resandable	2-3 times		CEN/TR14823		
Area Per Board	0.373 m <sup>2</sup>	Natural/Stained	Stained				
		Brinell Value	3,7		EN1533	NPD	
DETAIL DESCRIPTION		Joint	Woodloc® 5S	Strength N/mm <sup>2</sup> Thermal Conductivity	EN12664	0,14 W/mK	
All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.		Floor heating	Yes				
		Warranty	30 years				
		Wear-layer material	Hardwood	Thermal Resistance R-Value			.11 (m2K/W)
		Wear-layer thickness	3.5 mm				
		Core material	Pine/Spruce lamella	Biological	EN350-2	Class 1	
COLOUR CHANGE		Thickness	15 mm	Durability		Compliant	
Stained product - noticeable color change over time.		Installation method	Floating, Glue-down	CARB2			
		Surface Colour	Dark brown				

## CERTIFICATES

